



شركة الكحيمي للصناعات المعدنية المحدودة
Al Kuhaimi Metal Industries Ltd.

OPERATING PROCEDURE OF HOLLOW METAL DOORS AND FRAMES

A. GENERAL

A. The following procedures and information are supplied for the operation of Hollow Metal Doors and Frames.

B. Doors are equipped with latching mechanism.

DO NOT OPERATE LOCKING MECHANISM WHEN DOORS ARE IN THE OPEN POSITION.

C. Single swing doors are equipped with handles on the exterior side and a handle or panic bar on the interior side.

1. The key lock is on the exterior and latching is on the interior.
2. Turning interior handle or activating the panic bar will open door open if exterior is locked.

D. Double swing doors equipped with handles and/or panic bars on the active leaf.

1. The inactive leaf has a handle on the interior surface only.
2. The active leaf must be opened first and closed last.
3. Turning the interior handle or activating the panic bar on the active leaf will open the leaf even if the exterior is locked.

E. Safety Precautions to be observed.

1. Always make sure that the area in the immediate vicinity of door travel is clear of obstruction.
2. Areas contracted by seals must be continually kept free of debris and dirt.
3. Caution must be exercised to make sure that door is not closed when latching mechanism is extended.

Al Kuhaimi Metal Industries Ltd.
11th Street, First industrial city
P.O. Box 545, Dammam 31421, Saudi Arabia
Tel.: +966 13 847 2777
Fax: +966 13 847 2591
info@alkuhaimi.com

مجموعة الكحيمي
Al Kuhaimi Group
www.alkuhaimi.com